

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

STN Karlsruhe

L3 ANSWER 1 OF 1 WPIDS COPYRIGHT 2004 THOMSON DERWENT on STN

ACCESSION NUMBER: 1991-172376 [24] WPIDS

DOC. NO. NON-CPI: N1991-132053

DOC. NO. CPI: C1991-074484

TITLE: Cylindrical hollow body - with heat insulating jacket of microporous material with reduced pressure inside jacket.

DERWENT CLASS: A94 L02 Q67

INVENTOR(S): KRATEL, G; REISACHER, J; STOHR, G

PATENT ASSIGNEE(S): (WACK) WACKER CHEM GMBH

COUNTRY COUNT: 2

PATENT INFORMATION:

PATENT NO	KIND	DATE	WEEK	LA	PG	MAIN	IPC
DE 3940149	A	19910606	(199124)*				
ZA 9009728	A	19910925	(199145)				<--


APPLICATION DETAILS:

PATENT NO	KIND	APPLICATION	DATE
DE 3940149	A	DE 1989-3940149	19891205
ZA 9009728	A	ZA 1990-9728	19901204

PRIORITY APPLN. INFO: DE 1989-3940149 19891205

INT. PATENT CLASSIF.: C04B038-00; F16L059-06

GRAPHIC INFORMATION:



BASIC ABSTRACT:

DE 3940149 A UPAB: 19930928

A body is prepd. from a cylindrical hollow body, jacketted with a heat insulation based on a microporous heat insulation material, in which the pressure inside the jacket has been lowered to down to 10power(-6) bars.

The microporous heat insulation contains 20-100 (20-89) wt.% of finely divided metal oxide, 0-80 (10-70)% of inert filler, 0-50 (1-50)% of fibrous material, and 0-20 (0-10)% of hardener. The metal oxide is pyrogenic SiO₂ and/or Al₂O₃, opt. treated with a hydrophobising agent. The degree of deformation of the material used for the jacket is 1-100%. The article has several, pref. 1-10, layers.

ADVANTAGE - The heat insulation is incombustible, is formed from non-toxic materials, releases no toxic materials on heating, esp. on burning, has low heat conductivity, is impermeable to vapours, and is easily fixed.

1/1

FILE SEGMENT: CPI GMPI

FIELD AVAILABILITY: AB; GI

MANUAL CODES: CPI: A12-R06; L02-D15D